

Rekenwaarde maximum draagkracht in kN per sondering
Berekening volgens Eurocode 7-1 (NEN1997-1:2025)

diepte tov NAP	Sonderingen voor opdracht: 25SP1917										Stalen buispaal 0,219/0,219 m				
	DKM001	DKM002	DKM003	DKM004	DKM005	DKM006	DKM007	DKM008	DKM009	DKM010	DKM011	DKM012	DKM013	DKM014	DKM015
-8,50						152	180	159	135	131				180	
-9,00						161	200	175	152	143		250		220	
-9,50			136	139		169	201	197	213	164		349		365	
-10,00		316	166	194		386	211	345	275	189	285	385		350	
-10,50	84	341	200	201	125	362	230	442	298	194	352	410	281	317	
-11,00	228	365	299	256	148	342	274	460	392	205	421	435	369	315	
-11,50	273	390	412	363	269	347	285	475	425	215	446	459	394	366	83
-12,00														435	75
-12,50															
-13,00															
-13,50															
-14,00															
-14,50														423	298
-15,00														405	352
-15,50														405	329
-16,00														421	327
														474	338

Rekenwaarde maximum draagkracht in kN per sondering
Berekening volgens Eurocode 7-1 (NEN1997-1:2025)

Sonderingen voor opdracht: 25SP1917										Stalen buispaal 0,219/0,219 m			
	DKM016	DKM017	DKM018	DKM019	DKM020	DKM021	DKM022	DKM023	DKM024				
-8,50													
-9,00													
-9,50	193												
-10,00	321												
-10,50	352												
-11,00	221		85										
-11,50	174		143										
-12,00	153		216										
-12,50			251										
-13,00			228			73		98	122				
-13,50		130	200			202	171	190	189				
-14,00	322	83	205	135	69	270	223	216	250				
-14,50	346	75	200	128	71	270	198	248	248				
-15,00	334		200		160	229	201	288	242				
-15,50	309	122	206	146	160	217	202	289	254				
-16,00	308	134	269	154	170	228	214	296	294				

diepte tov NAP

Rekenwaarde maximum draagkracht in kN per sondering
Berekening volgens Eurocode 7-1 (NEN1997-1:2025)

Sonderingen voor opdracht: 25SP1917																	Stalen buispaal 0,273/0,273 m																
	DKM001	DKM002	DKM003	DKM004	DKM005	DKM006	DKM007	DKM008	DKM009	DKM010	DKM011	DKM012	DKM013	DKM014	DKM015																		
-8,50						210	253	221	191	191				255																			
-9,00						237	289	256	222	211		374		330																			
-9,50			198	207		243	286	288	318	238		509		536																			
-10,00		498	241	281		548	304	510	402	262	421	584		474																			
-10,50	130	529	285	287	174	488	327	627	425	275	511	615	420	448																			
-11,00	332	541	435	370	208	474	381	638	557	287	599	646	539	444																			
-11,50	393	590	581	520	387	477	400	639	607	299	645	677	566	518	118																		
-12,00														614	114																		
-12,50																																	
-13,00																																	
-13,50																																	
-14,00																																	
-14,50														548	429																		
-15,00														530	482																		
-15,00														529	442																		
-15,50														550	463																		
-16,00														623	476																		

diepte tov NAP

Rekenwaarde maximum draagkracht in kN per sondering
Berekening volgens Eurocode 7-1 (NEN1997-1:2025)

Sonderingen voor opdracht: 25SP1917		Stalen buispaal 0,273/0,273 m											
		DKM016	DKM017	DKM018	DKM019	DKM020	DKM021	DKM022	DKM023	DKM024			
-8,50													
-9,00													
-9,50	301												
-10,00	473												
-10,50	543												
-11,00	304			136									
-11,50	234			214									
-12,00	207			315									
-12,50				344									
-13,00				310			128		169	194			
-13,50		185	277				313	263	278	288			
-14,00	447	116	288		186	107	376	312	322	367			
-14,50	473	108	261		179	111	371	274	366	341			
-15,00	439		272			220	311	297	431	356			
-15,50	405	167	280		201	231	313	291	428	369			
-16,00	405	187	370		208	244	323	308	401	417			

diepte tov NAP

Rekenwaarde maximum draagkracht in kN per sondering
Berekening volgens Eurocode 7-1 (NEN1997-1:2025)

Sonderingen voor opdracht: 25SP1917		Stalen buispaal 0,324/0,324 m														DKM015
	diepte tov NAP	DKM001	DKM002	DKM003	DKM004	DKM005	DKM006	DKM007	DKM008	DKM009	DKM010	DKM011	DKM012	DKM013	DKM014	
-8,50							274	329	289	251	248				336	
-9,00							314	366	334	290	284		513		443	
-9,50				264	282		326	385	390	435	322		682		722	
-10,00			662	324	380		686	407	697	544	349	572	810		593	
-10,50	184	689	379	382	382	228	610	434	794	566	365	683	847	575	597	
-11,00	456	702	588	498	498	275	601	498	829	739	377	767	883	702	584	
-11,50	526	763	768	693	693	516	608	513	796	775	392	842	920	731	684	154
-12,00															809	149
-12,50																
-13,00																
-13,50																
-14,00															668	574
-14,50															659	635
-15,00															654	553
-15,50															682	597
-16,00															779	626

Rekenwaarde maximum draagkracht in kN per sondering
Berekening volgens Eurocode 7-1 (NEN1997-1:2025)

Sonderingen voor opdracht: 25SP1917										Stalen buispaal 0,324/0,324 m			
	DKM016	DKM017	DKM018	DKM019	DKM020	DKM021	DKM022	DKM023	DKM024				
-8,50													
-9,00													
-9,50	424												
-10,00	642												
-10,50	714												
-11,00	383		194										
-11,50	310		292										
-12,00	258		423										
-12,50			436										
-13,00			395			191		257	277				
-13,50		239	363			442	368	363	401				
-14,00	581	152	377	232	150	481	399	435	470				
-14,50	607	143	336	235	150	487	369	495	443				
-15,00	543		349		298	391	390	566	472				
-15,50	508	222	355	256	307	417	393	587	496				
-16,00	503	245	478	265	325	428	413	504	517				